

Silicone UL 3239 AWG 2 -8 150°C

Construction / Technical Data / Properties

- Conductor: tinned copper
- Outer diameter conductor: AWG 2 - 8
- Core insulation: silicone rubber
- Printing: acc. to UL-standard
- Colour: white, black and red are available
other colors on request
- temperature range: -40°C to +150°C
- flame retardant acc UL VW-1

small amounts (30,5m, 152m, 305m) are available at short notice

stocknumber: 778XX+colour

Ø Core mm ²	wire strength qmm	construction mm	curent voltage	Wall thickness mm	diameter mm	stocknumber
AWG 2	34,45	259 x 0,40	25 kV	1,57	11,76	778325+colour
AWG 4	21,55	133 x 0,45	25 kV	1,57	9,98	778325+colour
AWG 6	13,57	133 x 0,36	15 kV	1,14	7,70	778315+colour
AWG 6	13,57	133 x 0,36	25 kV	1,57	8,56	778325+colour
AWG 8	8,61	133 x 0,28	15 kV	1,14	6,58	778315+colour
AWG 8	8,61	133 x 0,28	25 kV	1,57	7,44	778325+colour
AWG 8	8,61	133 x 0,28	40 kV	2,46	9,22	778340+colour

- Weitere Anfertigungen auf Anfrage
- Alle Angaben ohne Gewähr