

Glass silk insulated pure nickel strand 400V, 1,50-10,0mm², + 400°C

Construction:

- Conductor: Pure nickel
- Construction: fine-stranded (see table)
- Insulation: covered with glass silk + impregnated glass silk braid
- Colour: white (natural), green/yellow (other colors on request)

Technical Data:

- Rated voltage: 400 V
- Test voltage: 2000 V
- Minimum bending radius fixed: approx. 18 x cable diameter
- Temperature range: -50°C to +400°C

| Dimension | Construction | Outside-Ø in mm | Article-Nr. |
|-----------|--------------|-----------------|----------------------|
| 1 x 1,50 | 30 x 0,25 | 2,90 | 8101015 white |
| 1 x 2,50 | 49 x 0,25 | 3,60 | 8101025 white |
| 1 x 4,00 | 84 x 0,25 | 4,40 | 8101040 white |
| 1 x 6,00 | 126 x 0,25 | 5,00 | 8101060 white |
| 1 x 10,00 | 203 x 0,25 | 6,20 | 8101100 white |
| 1 x 1,50 | 30 x 2,50 | 2,90 | 8101015 green/yellow |
| 1 x 2,50 | 49 x 0,25 | 3,60 | 8101025 green/yellow |
| 1 x 4,00 | 84 x 0,25 | 4,40 | 8101040 green/yellow |
| 1 x 6,00 | 126 x 0,25 | 5,00 | 8101060 green/yellow |
| 1 x 10,0 | 203 x 0,25 | 6,20 | 8101100 green/yellow |

- Weitere Anfertigungen auf Anfrage
- Alle Angaben ohne Gewähr