



UL 20711 cUL 4xAWG28+C+FEP sheath 300V 200°C 7x0,13mm OD=3mm +/-

Construction

• Conductor:	4xAWG28 (7x0,13mm)
• Insulation material:	FEP
• Insulation diameter:	0,8 +/- 0,1 mm
• Wall thickness:	0,20 mm
• Sheath wall thickness:	0,25 mm
• General shielding:	Tinned copper braid, approx. 80% coverage
• Core:	Style 10969-VW-1 cUL 28 AWG
• Nickel-plated copper core:	7/0.13 Cu Ni
• Outer diameter:	3 +/- 0,40 mm

Technical Data

• Test voltage:	between conductors 3 kV
• between shield and sheath 3 kV	
• Operating voltage:	300 V
• Temperature range:	-90°C +200°

Properties

- Excellent resistance to aggressive chemical environments.
- Excellent moisture and UV resistance.
- Excellent mechanical strength.

Standards:

- UL and cUL approval according to UL 758 and CSA C22.2 No. 210
- "Horizontal flame test" or according to UL approval
- FT1 "flame rating" according to cUL approval

Applications:

- Internal wiring of electric heaters
- External connections of electric heaters

The cable is manufactured according to UL specifications and is UL-printed.

Item number: 3501504281

-
- Weitere Anfertigungen auf Anfrage
 - Alle Angaben ohne Gewähr