

## HSLCH-JZ - 4,00 mm<sup>2</sup>

Halogen-free machine control cable with overall copper braided screening; preferred EMC compatible cable type

### Construction

- Conductor: stranded bare Cu conductor, fine wire
- Strand structure to VDE 0295 class 5 / IEC 60228 class 5
- Core insulation: halogen-free compound
- Black cores with printed consecutive number coding
- Green-yellow protective conductor (3 cores and over) in the outer layer
- Special versions without protective conductor: "OZ"
- Cross-sections 35.0 mm<sup>2</sup> and over with cores coloured to VDE 0293
- Cores twisted in layers, with optimal lay lengths
- Lapped with plastic film
- Braided screening made of tinned copper wire
- Outer sheath: halogen-free compound
- Sheath colour: RAL 7001 grey

### Technical Data

- Rated voltage: U<sub>o</sub>/U 300/500 V
- Test voltage: 4000 V
- Bending radius: 15 x cable diameter
- Temperature range:
  - flexible -15°C to +70°C
  - stationary -40°C to +70°C

### Properties

- Flame retardant to IEC 60332-3
- Halogen-free to IEC 60754-1 and IEC 60754-2

### Special characteristics

- reduced fire propagation
- low smoke emission
- low fire load
- no corrosiveness
- recyclable

Ø mm <sup>2</sup>	Cu-Weight kg/km	Outer-Ø mm	Total-Weight kg/km	Article number
2 x 4,0 OZ	163,0	10,0	233,0	2502400020
3 x 4,0	178,0	10,7	260,0	2503400000
4 x 4,0	248,0	11,8	280,0	2504400000
5 x 4,0	328,0	12,9	350,0	2505400000
7 x 4,0	371,0	14,2	490,0	2507400000

- Weitere Anfertigungen auf Anfrage

- Alle Angaben ohne Gewähr