

SiHF/Cu/Si-J - 0,50 mm²

Highly heat-resistant, silicone-sheathed flexible cable with overall copper braided screening

Construction

- Conductor: tinned Cu conductor, fine wire
- Strand structure to VDE 0295 class 5 / IEC 60228 class 5
- Silicone-insulated cores
- Cores coloured to VDE 0293
- 6 cores and over: black cores with printed consecutive number coding
- Green-yellow protective conductor (3 cores and over) in the outer layer
- Cores twisted in layers, with optimal lay lengths
- Lapped with foil
- Tinned copper braided screening
- Outer sheath: silicone
- Sheath colour: preferably reddish Brown

Technical Data

- Rated voltage: U₀/U 300/500 V
- Test voltage: 2.000 V
- Insulation resistance: ≥ 200 MΩm x km
- Bending radius: 20 x cable diameter
- Temperature range: -50°C to +180°C
temporarily up to +200°C

Properties

- Flame retardant to IEC 60332-1
- Halogen-free: HCl emission to IEC 60754-1
- Corrosiveness of combustion gas to IEC 60754-2

Ø Size mm ²	Cu-Weight kg/km	Outer-Ø mm	Total-Weight kg/km	Article number
2 x 0,75	37,5	8,9	104,0	8400020075
3 x 0,75	46,1	9,3	118,0	8400030075
4 x 0,75	57,3	10,2	152,0	8400040075
5 x 0,75	67,3	10,9	176,0	8400050075
7 x 0,75	103,0	11,5	215,0	8400070075

- Weitere Anfertigungen auf Anfrage
- Alle Angaben ohne Gewähr