

## SiHF/Cu/Si-J - 1,50 mm<sup>2</sup>

Highly heat-resistant, silicone-sheathed flexible cable with overall copper braided screening

### Construction

- Conductor: tinned Cu conductor, fine wire
- Strand structure to VDE 0295 class 5 / IEC 60228 class 5
- Silicone-insulated cores
- Cores coloured to VDE 0293
- 6 cores and over: black cores with printed consecutive number coding
- Green-yellow protective conductor (3 cores and over) in the outer layer
- Cores twisted in layers, with optimal lay lengths
- Lapped with foil
- Tinned copper braided screening
- Outer sheath: silicone
- Sheath colour: preferably reddish Brown

### Technical Data

- Rated voltage: U<sub>0</sub>/U 300/500 V
- Test voltage: 2.000 V
- Insulation resistance: ≥ 200 MΩm x km
- Bending radius: 20 x cable diameter
- Temperature range: -50°C to +180°C  
temporarily up to +200°C

### Properties

- Flame retardant to IEC 60332-1
- Halogen-free: HCl emission to IEC 60754-1
- Corrosiveness of combustion gas to IEC 60754-2

Ø Size mm <sup>2</sup>	Cu-Weight kg/km	Outer-Ø mm	Total-Weight kg/km	Article number
2 x 1,5	58,0	10,7	166,0	8400020150
3 x 1,5	74,0	11,2	188,0	8400030150
4 x 1,5	91,4	11,9	222,0	8400040150
5 x 1,5	121,7	13,1	273,0	8400050150
7 x 1,5	157,2	14,3	341,0	8400070150

- Weitere Anfertigungen auf Anfrage
- Alle Angaben ohne Gewähr