



LiYY UL/cUL 2464/2517-10002 AWG 20

Control cable unscreened

Construction

- Conductor: TPC - tin plated copper acc. EN 13602
- Stranding: AWG 20 - 7 x 0,320 mm
- Core insulation: PVC semi rigid
- Core diameter: 1,50 mm
- Outer sheath: UL-PVC 105°C
- Marking: printing and label

Technical Data

- Test voltage: 1.500 V
- Operating voltage UL: 300 V
- Conductor resistance: 37,400 Ω /km
- Temperature
range moved -10°C to +105°C
range static -30°C to +105°C

Properties

- flame retardant acc. to UL 1581 VW-1/ UL2556 FV-2
Style 2464 80°C, Style 2517 105°C

No. of cores	Outer diameter mm	Cu-Weight kg/km	Total weight kg/km	Article number
2	4,7	12,0	29,0	4040200200
3	4,9	17,0	39,6	4040200300
4	5,4	22,4	45,0	4040200400
6	6,3	33,5	63,0	4040200600
8	6,8	44,7	79,0	4040200800
10	7,7	56,0	102,0	4040201000
12	8,1	67,2	110,0	4040201200
14	8,5	78,4	127,1	4040201400
16	8,9	89,0	132,0	4040201600
18	9,4	99,0	168,0	4040201800

- Weitere Anfertigungen auf Anfrage
- Alle Angaben ohne Gewähr