



LiYY UL/cUL 2464/2517-10002 AWG 22

Control cable unscreened

Construction

- Conductor: TPC - tin plated copper acc. EN 13602
- Stranding: AWG 22 - 7 x 0,254 mm
- Core insulation: PVC semi rigid
- Core diameter: 1,30 mm
- Outer sheath: UL-PVC 105°C
- Marking: printing and label

Technical Data

- Test voltage: 1.500 V
- Operating voltage UL: 300 V
- Conductor resistance: 59,400 Ω /km
- Temperature
range moved -10°C to +105°C
range static -30°C to +105°C

Properties

- flame retardant acc. to UL 1581 VW-1/ UL2556 FV-2
Style 2464 80°C, Style 2517 105°C

No. of cores	Outer diameter mm	Cu-Weight kg/km	Total weight kg/km	Article number
2	4,3	7,0	23,0	4040272201
3	4,5	10,0	26,7	4040372201
4	4,8	14,6	33,0	4040472201
6	5,7	19,8	47,0	4040672201
8	6,2	27,2	59,0	4040872201
10	6,9	34,0	71,0	4041072201
12	7,2	48,0	80,0	4041272201
14	7,6	46,7	89,6	4041472201
16	8,0	56,0	100,7	4041672201
18	8,2	60,0	108,6	4041872201

- Weitere Anfertigungen auf Anfrage
- Alle Angaben ohne Gewähr