



LiYY UL/cUL 2464/2517-10002 AWG 28

Control cable unscreened

Construction

- Conductor: TPC - tin plated copper acc. EN 13602
- Stranding: AWG 28 - 7 x 0,127 mm
- Core insulation: PVC semi rigid
- Core diameter: 0,90 mm
- Outer sheath: UL-PVC 105°C
- Marking: printing and label

Technical Data

- Test voltage: 1.500 V
- Operating voltage UL: 300 V
- Conductor resistance: 239,000 Ω /km
- Temperature
range moved -10°C to +105°C
range static -30°C to +105°C

Properties

- flame retardant acc. to UL 1581 VW-1/ UL2556 FV-2
Style 2464 80°C, Style 2517 105°C

No. of cores	Outer diameter mm	Cu-Weight kg/km	Total weight kg/km	Article number
2	3,6	1,8	14,6	4040280200
3	3,7	2,7	16,7	4040280300
4	3,9	3,6	19,0	4040280400
5	4,1	4,3	19,9	4040280500
6	4,4	5,5	24,00	4040280600
8	4,6	7,3	28,80	4040280800
10	5,3	9,0	32,19	4040281000
12	5,6	10,9	36,4	4040281200
14	5,8	12,7	40,70	4040281400
16	5,9	14,5	45,00	4040281600

No. of cores	Outer diameter mm	Cu-Weightkg/km	Total weight kg/km	Article number
18	6,2	16,3	49,50	4040281800

- Weitere Anfertigungen auf Anfrage
- Alle Angaben ohne Gewähr